



GH PLANT

GH64, GH94 & GH1054

GH64

This is the smallest of the GH plant trailer range. With a bed size of 6' x 4' wide and a payload of 1230kg (gross weight 1500kg), the GH64 is designed for smaller items of plant such as micro-excavators.

Compact yet robust, this is a neat and convenient single axle trailer that can be towed behind a car and is easily manoeuvred by hand when loaded.

As with all GH models, its galvanized welded construction and leaf spring suspension ensures it will withstand tough conditions.

GH64 model is available with two ramp options, a 3'9" ramp with mesh infill or a longer 4'9" bevelled ramp with no infill.

GH94

The GH94 is an extremely versatile plant trailer. A 24mm thick platform makes the GH94 particularly suitable for transporting a wide selection of plant, including tracked excavators, and many items of wheeled equipment such as rollers.



GH64 with 4'9" bevelled ramp



GH94 with 195/55R10C tyres and 3'9" ramp with mesh infill



GH94BT with 165R13C tyres and 4'9" bevelled ramp



Two self supporting knife edge ramp options are available on all GH models. The 3'9" mesh infill ramp (see opposite) provides the benefits of a full width ramp. The 4'9" bevelled ramp offers significant benefits when loading plant - As well as a 13° loading angle, the ramp is bevelled to help guide the tracks or wheels of the plant being loaded, which provides reassurance to the operator.

GH1054 with 4'9" bevelled ramp

GH94

cont. . .

The 9' length of the GH94 provides ample loading space behind the rear axle. This enables a full range of mini-excavators to be loaded along with machines with a more central centre of gravity, such as hi-tip dumpers.

The GH94 is available with 195/55R10C tyres, or larger 165R13C tyres. Trailers with larger tyres are constructed to a beavertail specification to maintain the excellent loading angle of 13°. Beavertail models are also 3" wider than flatbed models.

GH94 models on both 10' and 13' tyres are offered with either the 3'9" ramp with mesh infill or the 4'9" bevelled ramp with no infill.

Both GH94 models are available with a patented breaker storage option. Further details can be found overleaf.

GH1054

The GH1054 offers one of the highest payloads ever produced by Lfor Williams Trailers. With its robust, welded construction and heavily treaded 185/70R13C tyres, the GH1054 is a rugged trailer for demanding conditions.

To provide the highest possible payload, the GH1054 floor construction is suitable only for tracked excavators.